



## Self Cross-linking Urethane Gym Floor Coating

LowPost is a self cross-linking gym floor coating that has been formulated for ease of use without sacrificing performance. LowPost exhibits outstanding gloss and depth of image. It is an eco-friendly water-based urethane alternative to traditional solvent based systems. LowPost is EPA and SCAQMD VOC-compliant.

### Product Advantages

- High Gloss
- Excellent Depth of Image
- High Solids
- Low odor
- Very good hardness & flexibility
- Very good gloss retention
- Resistant to yellowing
- Fast in service time
- Water clean-up
- VOC compliant: per EPA and SCAQMD regulation standards established for gym floor coatings

### Physical Characteristics

Gloss: 90° ± 2 @ 60° angle

Volume Solids: 32±2%

Weight Solids: 34±2%

Shelf Life: one year

Application Equipment: T-Bar—light or heavy weight bar

Dry time: 2-3 hours at 75°F and 50% R.H.

Recoat: After 6 Hours and before 3 days—screen after 3 days

Theoretical Coverage: 519 SF/gal @ 1 mil wet

Recommended Coverage: 450-550 SF/gal

VOC's: <250 g/l

### Application Recommendations

\*See Praetorian Wood Floor Application Guide for application instructions\*

1. Prepare floor according to application guide
2. Apply 1-2 coats of FCP Sealer
3. Line strip with Praetorian BaseLine line stripe coating, if needed
4. Apply 2-3 coats of LowPost

Allow to dry 24 hours before use after final coat

### Packaging and Product Order Information

Item Description: LowPost Gym Floor Coating

Item Code Number: CF-0623

Packaged as: Five-Gallon Box (2) 2-1/2 gallon plastic jugs per box

Shipping Information: DOT NON-regulated