

# MIGHTYONE HD™

## WATER REDUCIBLE HIGH PERFORMANCE URETHANE

MightyOne HD is an ultra-durable floor finish that exhibits long service life without buffing or burnishing. MightyOne HD will reduce: floor finish labor, water consumption and waste stream contribution. MightyOne HD urethane is semi-permanent and strippable with U<sub>2</sub>O Remover.

Excellent adhesion to VCT, terrazzo and other flexible/resilient floor surfaces.

### PRODUCT ADVANTAGES

- NO HEAVY-METALS / ZINC-FREE
- Strippable—Prætorian U<sub>2</sub>O Remover
- No more buffing or burnishing
- Save thousands of hours annually
- One coat application
- Appearance of 6+ coats of acrylic finish
- 4-6 hour dry time ~ Faster than 6 coats of acrylic!
- Three hour working pot-life
- Extreme hardness & flexibility
- Extreme scuff, mar and wear resistance
- Outstanding chemical & stain resistance
- Outstanding gloss retention
- Resistant to yellowing
- Excellent early moisture resistance
- Very low odor
- Water clean-up
- Meets EPA, CARB, and OTC VOC regulations



### APPLICATION AREAS

- Hospitals, Surgical Care Centers
- Clinics & Care Centers
- Nursing Homes & Assisted Living Facilities
- Offices & Apartment Common Areas
- Schools, Colleges, Universities
- Daycares
- Laboratories & Research Centers
- Restaurant Kitchens/Cafeterias
- Entertainment & Retail: Casinos, Airports
- Fitness Centers
- Correctional Facilities

# PRÆTORIAN

## URETHANE FLOOR FINISH SYSTEM



**STEPONE** seals the surface allowing enhanced gloss, depth-of-image and ease in stripping of Prætorian urethane floor finishes. Use before MightyOne HD, MightyOne T-Bar, or 2010 UD urethane finishes.

### MIGHTYONE HD

**Gloss** MightyOne HD is a spectacular floor finish. MightyOne HD Gloss measures 90°+ @ 60° angle with outstanding Depth-of-Image (DOI).

**Semigloss** is recommended where a lower sheen is desired or because of floor surface defects. MightyOne HD Semigloss has a gloss of 45-50° @ 60° angle. The lower sheen is more forgiving where surface imperfections may be distracting.

**Matte** finish is especially suitable for areas where a low degree of light reflection is important, such as nursing homes and assisted living care facilities as well as hallways and common public areas.

**MIGHTYONE T-BAR** can be applied up to 10,000 SF per hour. Specifically formulated for T-Bar application with near the performance of MightyOne HD.

**2010 UD FAST DRY** meets CARB's 2010 year end VOC regulations of less than 1% per gallon. 2010 UD has very fast dry and recoat times (±1 hour). Up to a gloss of ± 95° @ 60° angle, with DOI matching MightyOne HD. No buffing or burnishing required. 2010 UD provides regulatory peace of mind with superior performance.

**TITANBOOST** is a very low odor companion product to U<sub>2</sub>O Remover. TitanBoost will increase the effectiveness of U<sub>2</sub>O Remover throughout the removal process. TitanBoost is also very effective as a pre-clean before finishing.

**LIFTOFF** is an extremely fast and effective urethane and acrylic remover. Stripping times, for urethane blended acrylics, are less than 10 minutes!

**U<sub>2</sub>O REMOVER** is formulated specifically to strip urethane floor finishes, from two component, three component and UV cure. Fast working & low odor, U<sub>2</sub>O Remover is unequalled in the market place today.

Distributed by: