



Gym Floor Finish

High Quality Two-component Water-reducible High Performance Gym Floor Finish

PointGuard is a high quality water-based urethane. Especially formulated for gym floor applications. PointGuard exhibits a high gloss with nice depth of image. It is an eco-friendly water-based urethane alternative that will rival traditional solvent based systems in performance. PointGuard is EPA VOC-compliant. Due to the higher solids of PointGuard, fewer may be required compared to traditional Gym/Wood Floor Coatings.

Product Advantages

- High Gloss
- Depth of Image
- High Solids: Possibly fewer coats with excellent durability
- Low odor
- Chemical & stain resistance
- Resistant to yellowing
- EPA VOC Compliant
- Passes OSHA standards for Slip Coefficient of Friction (SCOF)

Physical Characteristics

Gloss: 85-90° @ 60° angle

Volume Solids: 33± 2%

Weight Solids: 35± 2%

Pot Life: 18 hours

Mixing Time: 5-7 minutes with a jiffy mixer

Application Equipment: T-Bar

Dry time: 6 Hours at 75°F and 50% RH

Recoat: After 8 Hours and before 3 days—screen after 3 days

Coverage: 500-550 SF per gallon kit

Packaging

Product Code: CF-0546

Description: PointGuard Gym Floor Finish

Packaged as: 5-Gallon Kit

Mixing Instructions

1. Open Part A.
2. Pour Part B into Part A, drain Part B container as much as reasonably possible.
3. Use a drill and jiffy-type mixing blade to mix Part A and B together.
4. Mix for a 5-7 minutes.
5. Mark start time on the container to keep track of useable working (pot-life eighteen hours) time.
6. Cover container until time of use.
7. For complete instructions on application, follow instructions in Wood Floor Application Guide.