



Premium Gym Floor Finish

The Industries Premier Two-component Water-reducible High Performance Gym Floor Finish

PowerForward is a premium water-based aliphatic urethane. Especially formulated for gym floor applications. PowerForward exhibits exceptional gloss and depth of image. It is an eco-friendly water-based urethane alternative that will rival traditional solvent based systems. PowerForward is EPA VOC-compliant. Due to the higher solids of PowerForward™, fewer coats are required compared to traditional Gym/Wood Floor Coatings.

Product Advantages

- Exceptional High Gloss
- Exceptional Depth of Image
- High Solids: Fewer coats with superior durability
- Low odor
- Excellent chemical & stain resistance
- Outstanding resistance to yellowing
- EPA VOC Compliant
- Passes OSHA standards for Slip Coefficient of Friction (SCOF)

Physical Characteristics

Gloss: 85-90° @ 60° angle

Volume Solids: 35± 1%

Weight Solids: 38± 1%

Pot Life: 3 hours

Mixing Time: 5-7 minutes with a jiffy mixer

Application Equipment: T-Bar—Light Weight Bar preferred

Dry time: 6 Hours at 75°F and 50% RH

Recoat: After 8 Hours and before 3 days—screen after 3 days

Coverage: 500-550 SF per one unit kit

Packaging

Product Code: CF-0513

Description: PowerForward Gym Coat

Packaged as: Four-Unit Kit: Part A—5-gal size container & Part B—64oz. F-style container

Mixing Instructions

1. Open Part A.
2. Pour Part B into Part A, drain Part B container as much as reasonably possible.
3. Use a drill and jiffy-type mixing blade to mix Part A and B together.
4. Mix for a 5-7 minutes.
5. Mark start time on the container to keep track of useable working (pot-life three hours) time.
6. Cover container until time of use.
7. For complete instructions on application, follow instructions in Wood Floor Application Guide.