



# TITANBOOST™

## Product Overview

Urethane finishes generally are more difficult to remove. Praetorian has developed a remover system that has been tested successfully to remove nearly all type of urethane finishes, including UV-cure. TitanBoost was formulated to aid and speed up the removal of urethane finishes when using Praetorian's U<sub>2</sub>O Remover.

- Use as a "pre-prep"
- Use to rewet stubborn areas after U<sub>2</sub>O application.
- Prediluted— ready to use
- Will not damage VCT, linoleum type, or vinyl\*
- Easily applied using a micro-fiber type mop
- NON-CORROSIVE—more user friendly, pH below 10.6
- Very low-odor
- Water clean-up

## Application Process

\*Always test this product in an inconspicuous area before use.  
Consult Praetorian or representatives for questions or recommendations

1. SHAKE container BEFORE USING.
2. Pour TitanBoost on floor.
3. Spread TitanBoost with a microfiber mop.
4. Allow product to stand 5-10 minutes.
5. Abrade surface with 150 grit screen using a low speed floor machine.
6. Extract excess product.
7. Pour U<sub>2</sub>O on the pre-prepped floor (follow label instructions).
8. Allow sufficient U<sub>2</sub>O dwell time.
9. With a low speed floor machine, using the recommended stripping pad for surface type, work the loosened old finish from the surface.
10. As needed, pour out more TitanBoost on to surface previously coated with U<sub>2</sub>O.
11. Continue working product loose from the floor with the floor machine.
12. Extract remover solution(s) from the floor.
13. Follow U<sub>2</sub>O procedures for removal and clean-up.

## Technical Data

Non-Corrosive: PH: 10.0-10.6

VOC's: Zero VOC's; EPA and CARB Consumer Goods Regulations

Shipping Information: DOT Not Regulated

HMIS Data: Health 2; Flammability 1; Physical Hazard 0; Personal Protection B

Coverage: Approx. 1000 SF per gallon