



## High Solids Wood Sealer

ZonePress is a unique formula, representing the best in water-based wood floor sealers. It is VOC Compliant nationally. ZonePress is very user friendly in application and odor. ZonePress, unlike most water-based sealer, has minimal to no grain lift! ZonePress also has a short recoat time, enabling a double coat or topcoat in one day.

### Product Advantages

- High build, high solids sealer
- Very Fast Dry
- Excellent Flow and Leveling
- Good open time for T-Bar application
- No critical recoat time, after dry
- Very Low odor
- Excellent sandability
- Water clean-up
- Compliant VOC—EPA and SCAQMD

### Physical Characteristics

Volume Solids: 33%  $\pm 2\%$

Weight Solids: 35%  $\pm 2\%$

VOC's: <250 grams per liter

Coverage: 400 to 550 square feet per gallon, depending on surface porosity

Dry to touch: 1 to 2 hours

Recoat: After 4-5 hours

Sand: After 4-5 hours

Clean Up: Water

### Packaging

Product Code: CF-0592

Description: ZonePress Wood Sealer

Packaged as: Box (5gl)

### Application Recommendations

\*Consult Praetorian Protective Finishes Wood Floor Application Guide for detailed instructions.

1. Apply @ Temperature: 65° to 80° and not above 85% RH
2. Thoroughly plan out the application before starting.
3. Keep air flow to a minimum, flash drying will effect proper leveling.
4. Use a high quality T-Bar applicator pads. A heavyweight bar is preferred, for heavier build use a lightweight T-bar.
5. Allow to dry four (4) hours before applying additional coat or top coat.